

# UNITAP™ MINI-TAP

## Connectors for Code and Flex Conductor

The UNITAP™ MINI-TAP stands out in the market with its versatile and efficient design, tailored to meet the diverse needs of electrical connections.

This innovative product is uniquely engineered to facilitate seamless splices between Al to Al, Al to Cu, and Cu to Cu wires, making it a superior choice for a wide range of applications.



### Features & Benefits

- Accepts Aluminum / Copper Conductor
- One piece for easy, safe installation
- Max. Voltage: 300V
- Tin-Plated Connector for corrosion resistance
- Robust Steel Set Screws for enhanced reliability
- cULus 486C Listed for US and Canadian Markets
- UL 467 Listed
- Wire Range: #18-#6 Str, #18-8 Sol (Al/Cu)
- Wire Range: #18-#6 Cu Class G, H, I, K, DLO

Catalog Number	No. of Ports	Product Dimensions			Conductor Range	Color
		Overall Width	Overall Length	Overall Height		
BMT62B	2	1.07"	.96"	.76"	#18-#6 Str, #18-8 Sol (Al/Cu)  #18-#6 Cu Class G, H, I, K, DLO	Brown
BMT62P	2	1.07"	.96"	.76"		Purple
BMT62BBOX100	2	1.07"	.96"	.76"		Brown
BMT62PBOX100	2	1.07"	.96"	.76"		Purple
BMT62BBOX1000	2	1.07"	.96"	.76"		Brown
BMT62PBOX1000	2	1.07"	.96"	.76"		Purple
BMT63B	3	1.07"	1.31"	.76"	#18-#6 Str, #18-8 Sol (Al/Cu)  #18-#6 Cu Class G, H, I, K, DLO	Brown
BMT63P	3	1.07"	1.31"	.76"		Purple
BMT63BBOX100	3	1.07"	1.31"	.76"		Brown
BMT63PBOX100	3	1.07"	1.31"	.76"		Purple
BMT63BBOX1000	3	1.07"	1.31"	.76"		Brown
BMT63PBOX1000	3	1.07"	1.31"	.76"		Purple